



Environmental Onsite Wastewater Solutions®

Nevada Sizing Chart for Disposal Field Systems

Percolation Rate (min/in)	Septic Tank Size											
	1000 Gallon Tank 3 Bedrooms or Less				1250 Gallon Tank 4 Bedrooms				1500 Gallon Tank 5 or 6 Bedrooms			
	Quick4 Equalizer 24 1.5' Wide Trench	Quick 4 Equalizer 36 2' Wide Trench	Quick 4 Standard 3' Wide Trench	Quick4 High Capacity 3' Wide Trench	Quick4 Equalizer 24 1.5' Wide Trench	Quick4 Equalizer 36 2' Wide Trench	Quick 4 Standard 3' Wide Trench	Quick4 High Capacity 3' Wide Trench	Quick4 Equalizer 24 1.5' Wide Trench	Quick4 Equalizer 36 2' Wide Trench	Quick 4 Standard 3' Wide Trench	Quick4 High Capacity 3' Wide Trench
	3.43	5.29	6.19	7.14	3.43	5.29	6.19	7.14	3.43	5.29	6.19	7.14
	16" W 4.0' L	22" W 4.0' L	34" W 4.0' L	34" W 4.0' L	16" W 4.0' L	22" W 4.0' L	34" W 4.0' L	34" W 4.0' L	16" W 4.0' L	22" W 4.0' L	34" W 4.0' L	34" W 4.0' L
10 or less	46	30	26	22	57	37	32	28	69	45	38	33
11-15	57	37	32	27	71	46	39	34	85	55	47	41
16-20	67	43	37	32	83	54	46	40	100	65	56	48
21-25	73	48	41	36	92	60	51	44	110	71	61	53
26-30	82	53	45	39	102	66	57	49	122	79	68	59
31-40	92	60	51	44	114	74	64	55	137	89	76	66
41-50	105	68	58	51	131	85	73	63	157	102	87	76
51-60	122	79	68	59	152	99	85	73	183	119	101	88

Minimum number of chambers required per dwelling is 22 chambers. Please refer to sizing chart.

PO Box 768, Old Saybrook, CT 06475

860-577-7000 Fax 860-577-7001

1-800-221-4436

www.infiltratorsystems.com

APPROVED JUN 28 2006